
PFAS: The CFPUA Experience





Introduction to CFPUA

- Serve approximately 200,000 people in Wilmington and New Hanover County
- Annually deliver 7 billion gallons of water
- Annually collect 6.6 billion gallons of wastewater
- Average water production: 19.2 million gallons per day







_


2017: Five-year Odyssey Begins



Wilmington StarNews front page, June 8, 2017

- Sparked crisis of confidence in safety of drinking water
- Communitywide call for steps to address contamination
- Legal action against Chemours and DuPont (ongoing)
- CFPUA staff directed to identify and implement effective treatment solution as promptly as possible

PFAS Solution Timeline



Sweeney Water Treatment Plant

- 1. Raw Water Ozonation
- 2. Superpulsators
- 3. Intermediate Ozonation
- 4. Biofiltration with GAC
- 5. Deep Bed GAC Contactors
- 6. UV Disinfection
- 7. Finished Chemical Addition
- 8. Clear wells
- 9. High-Service Pump Station
- 10. Backwash and Residuals Handling



Contactor Design Summary

Granular Activated Carbon Contactor Design Summary

Number of GAC Contactors

Design Flow Rate (each)

Type

Size (each)

GAC Media Depth

Contact Time at Design Flow

8

3,823 GPM

Concrete Basin

22 x 38 feet

12.5 feet

20 minutes



Contactor Construction Summary

Schedule:

- Study/Pilot testing 12 months
- ♦ Design 9 months
- ♦ Construction 36 months
- ♦ Optimization 12+ months

Construction Cost:


- **▶** Bid \$35,915,000 (2019)
- ▶ Final construction \$36,084,104

Total Project Cost: \$43 million





GAC Treatment Operations


- ► GAC removes PFAS from water through a process called adsorption (with a "d")
 - ► Water flows over the GAC and PFAS compounds cling to the surface area of GAC particles
- GAC media must be periodically regenerated to maintain high level of PFAS removal
- ► Operationally 10-11 GAC media exchanges per year
 - Carbon taken offsite by vendor for "regeneration" (PFAS destroyed by exposing GAC to extreme temperatures)
 - ► 60-day turnaround per filter
 - ▶ Dry GAC Media = 8 truck loads
 - ► Wet GAC Media = 16 truck loads





GAC Performance: PFAS MCLs and Hazard Index











GAC Operating Costs – By the Numbers


 The operating cost for the new Granular Activated Carbon facility

► Reactivation Cost \$395,543 each

Virgin Makeup up to 15% (\$2.29/lb)

Transportation Price Deduction (per qualifying contactor)


Annual GAC reactivation cost: \$4,112,000



GAC Operation and Maintenance Costs		Actual Cost
Annual electrical cost		\$46,000
Annual O&M cost (labor/other)		\$179,000
Annual facility insurance cost		\$98,000
Annual GAC reactivation cost		\$4,112,000
	TOTAL	\$4,435,000

Key Takeaways

- Design for operational flexibility
- Choose your trigger carefully: Account for public expectations and regulatory expectations, but recognize cost impacts
- Recognize the scale: 8 (dry) to 16 (wet) truckloads per basin
- Impact to average customer's bill: \$5.88/month or \$70.56/year
- Have a robust PFAS monitoring and communications plan



Questions?

